



<b>1/2" 1.4/ 6 mm C</b>		<b>1/3"</b>	
Focal Length	f=6mm±5%		
Max. Diameter (Ratio)	F=1 : 1.4±5%		
Element	6 Group 7 Elements		
Picture Size	4.8x6.4mm		3.6x4.8
Angle	Ver.	44.0°	33.7°
	Hor.	57.3°	44.2°
	Dia.	69.4°	54.4°
Distortion (TV)	-1.0%		
Shooting Range at M.O.D.	Ver.	128mm	
	Hor.	174mm	
	Dia.	221mm	
Minimum Object Distance	0.2m		
Flange Back	12.5 mm in air		
Back Focus	9.46mm in air		
Filter Screw Size	M30.5x0.5		
Front/Rear Effective Dia.	F: φ 16.2mm		R: φ 8.7mm
Mount	C-MOUNT		
Exit Pupil	-77.3mm		
Temperature Range	-10~+45° C		
Storage Temperature Range	-40~+60° C		
Resolution	Center: 100 LP/mm		Corner: 40LP/mm
Stopper strength	10kgf ▪ cm		
Endurance Tests	Iris: 5,000Times		Focus: 5,000Times
Operating Torque	Iris: 50~600gf ▪ cm		Focus: 100~1000gf ▪ cm
Weight	63g±5g		

LM6NCR